	SHEET REV ECO DATE	DESCRIPTIO	N	BY APR CHK
	,	INISH WAS BLACK POWDER COAT		MR MR LS
		DDED -2 ASSY. AND -11 CAP		GP GP LS
		HT1 ADDED LOCKTITE#81794, SHT2 ADDED 0		REB REB LS
	1,3   D   10/29/2012   A	ADDED SHT 3, -3, -412, -13, UPDATED BE	IM. 0.75 DIMS WERE .XXX	DGW
IR-1070-11 C IR-1070-12 C IR-1070-13 C — MS21059L MS3		2 PLCS)		
	-CONFIDENTIAL: THE INFORMATION AND DATA CONT. S PROPRIETARY AND IS SUBMITTED IN D. SHALL NOT BE DISCLOSED, USED OF R ANY PURPOSE WHATSOEVER WITHOU	WHERE NOTED:  .X = ± .1  .XX = ± .05  .XXX = ± .010  ANGLES - + 1°		

## RELEASE DATE 2023.05.30 - REF ECR 521

MATERIAL: AL 6061-T6 PER QQ-A-250/11 AMS 4027 STOCK: 3/4" PLATE OR 3" BAR FINISH: BLACK ANDDIZE PER MIL-A-8625 TYPE II, CLASS 2 WEIGHT: 0.47 lbs SURFACE FINISH 125 ø2.835 - DRILL Ø0.125 X 0.250 DEEP - DRILL Ø0.125 X 0.250 DEEP Ø3.000-Ø3.000--ø2.835 DRILL & TAP #4-40UNC R0.450 DRILL & TAP X 0.250 DEEP" Ø1.085-Ø1.09-#4-40UNC 0.968 0.250 MIN NOMINAL 1.567 THREAD DEPTH 1.000 100° 100° (TYP. 2 PLCS) Ø0.257-Ø0.257-R0.325 -0.220-0.220<del>--</del>1.000→ -0.458 -0.458 -0.75-0.75 -10 CAP -11 CAP Paravion<sup>®</sup> TITLE DRAWING NO. √Technology IR-1070 CAP ASSEMBLY DIMENSIONS IN INCHES DRAWN APRVD. CHK'D TOLERANCES EXCEPT WHERE NOTED: DATE REV ECO BYBYBYRHSM REB REB 09/06/96 D  $.X = \pm .1$  $.XX = \pm .05$ -CONFIDENTIAL INFORMATION-THE INFORMATION AND DATA CONTAINED HEREIN PROTO  $.XXX = \pm .010$ DO NOT SCALE DRAWING SHEET IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE; ANGLES = ± 1° AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED THREADS: © 2001 PARAVION TECH., INC. N/C INTERNAL=CLASS 2B PARAVION IS A TRADEMARK OF EXTERNAL=CLASS 2A PARAVION TECHNOLOGY, INC. 2 DF 3 FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR BREAK ALL SHARP EDGES WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

